

Product information*

CENTRAL HYDRAULIK FLUID



Description

CHF is a multi-purpose synthetic hydraulic fluid for the central hydraulic system of a car. It has a low pour point and high viscosity index and can be used all year round. It is compatible with all types of hoses and seals. It is also suitable for power steering, level-controlled hydropneumatic suspension systems, shock absorbers, anti-lock brakes (ASR) and stability control (ESC), engine shutdown systems, hydrostatic fan drive systems, air conditioning pumps, central locking systems and central locking.



Also recommend this product for vehicles or assemblies for which the following specifications or original part numbers are required

VW TL 52 146 / G 002 000 / G 004 000, VOLVO 1161529-1 / 8713089, MAN M 3289, FORD WSS-M2C204-A, BMW 81 22 9 407 758, FENDT X 902.011.622, GM/OPEL B 0400070, FIAT 9.55550-AG3, ZF TE-ML 02K/09B, MB 345.0, Others CHF 202/11S

Technical data*

Viscosity at 100 °C	ASTM D 445 5,59 mm ² /s
Viscosity index	ASTM D 2270 TS ISO 2909 130
Solidification temperature	ASTM D 97 -26°C
Density at 15 °C	ASTM D 1298 0,860 g/cm ³

Available pack sizes

1L Canister plastic	AU7783-1
---------------------	----------

*The document is for informational purposes and is not an official certificate. The data is based on production control and corresponds to the product's characteristics at the time of manufacture.

AUTOLIVE 2015 S.L.
Av. Fuentemar 43, Nave 9-A
28823 COSLADA, MADRID - ESPAÑA

Nika-Trade LLP, 35a Almatyskaya str,
m. Kyiv, 02092, Ukraine
+38(044) 500-55-04

AUTOLIVE