

# Product information\*

## CLASSIC 10W-40



### Description

CLASSIC 10W-40 is a high-performance semi-synthetic low-friction engine oil with SAE 10W-40 viscosity grade, made from a mixture of mineral and synthetic base oils. It is recommended for year-round use in petrol and diesel engines, including turbocharged engines. Thanks to the technologically advanced selection of the additive package, selected base oils and viscosity properties, it contributes to economical engine operation.



### Specifications / Approvals

API SL/CF, ACEA A3/B4

**Also recommend this product for vehicles or assemblies for which the following specifications or original part numbers are required**

VW 501.01/505.00, MB 229.1

### Technical data\*

Viscosity at 100 °C	ASTM D 445 14,29 mm <sup>2</sup> /s
Viscosity index	ASTM D 2270 TS ISO 2909 153
Solidification temperature	ASTM D 97 -30°C
Density at 15 °C	ASTM D 1298 0,869 g/cm <sup>3</sup>
TBN	ASTM D2896 TS 5655 ISO 3771 10,3 mgKOH/g

### Available pack sizes

1L Canister plastic	AU8009-1
4L Canister plastic	AU8009-4
5L Canister plastic	AU8009-5
10L Canister plastic	AU8009-10
20L Canister plastic	AU8009-20
200L Barrel	AU8009-200

**UFI:** EP20-KOQ1-800X-AW78

\*The document is for informational purposes and is not an official certificate. The data is based on production control and corresponds to the product's characteristics at the time of manufacture.

**AUTOLIVE 2015 S.L.**  
Av. Fuentemar 43, Nave 9-A  
28823 COSLADA, MADRID - ESPAÑA

**Nika-Trade LLP, 35a Almatyskaya str,**  
m. Kyiv, 02092, Ukraine  
+38(044) 500-55-04

**AUTOLIVE**