

Product information*

DIESEL HIGH 10W-40



Description

DIESEL HIGH 10W-40 is a semi-synthetic high-performance, low-friction engine oil with SAE 10W-40 viscosity class, made from a mixture of mineral and synthetic base oils. It is recommended for all-season use in passenger diesel and petrol engines, including those with turbocharging. Thanks to the high-tech selection of the additive package, selected base oils and viscosity properties, it contributes to fuel-saving engine operation.



Specifications / Approvals

API CH-4/SL, ACEA A3/B4

Also recommend this product for vehicles or assemblies for which the following specifications or original part numbers are required

VW 501.01/505.00, MB 229.3, RENAULT RN 0700/RN 0710

Technical data*

Viscosity at 100 °C	ASTM D 445 14,29 mm ² /s
Viscosity index	ASTM D 2270 153
Solidification temperature	ASTM D 97 -30°C
Density at 15 °C	ASTM D 1298 0,869 g/cm ³
TBN	ASTM D2896 TS 5655 ISO 3771 10,3 mgKOH/g

Available pack sizes

1L Canister plastic	AU7782-1
5L Canister plastic	AU7782-5
10L Canister plastic	AU7782-10
20L Canister plastic	AU7782-20
200L Barrel	AU7782-200

UFI: NS20-30DE-KOOF-07TA

*The document is for informational purposes and is not an official certificate. The data is based on production control and corresponds to the product's characteristics at the time of manufacture.

AUTOLIVE 2015 S.L.
Av. Fuentemar 43, Nave 9-A
28823 COSLADA, MADRID - ESPAÑA

Nika-Trade LLP, 35a Almatyskaya str,
m. Kyiv, 02092, Ukraine
+38(044) 500-55-04

AUTOLIVE