

Product information*

ELITE 5W-40



Description

ELITE 5W-40 is a universal fully synthetic motor oil for petrol and diesel engines with and without turbocharging. The high technological efficiency of production allows you to get optimal performance from the engine and helps to increase engine life. It provides a high level of wear protection and has excellent cold start properties.



Specifications / Approvals

API SN/CF, ACEA A3/B4

Also recommend this product for vehicles or assemblies for which the following specifications or original part numbers are required

Opel GM-LL-B-025, VW 502.00/505.00, MB 229.3, Renault RN 0700/0710

Technical data*

Viscosity at 100 °C	ASTM D 445 15,56 mm ² /s
Viscosity index	ASTM D 2270 TS ISO 2909 173
Solidification temperature	ASTM D 97 -35°C
Density at 15 °C	ASTM D 1298 0,852 g/cm ³
TBN	ASTM D2896 TS 5655 ISO 3771 7,6 mgKOH/g

Available pack sizes

1L Canister plastic	AU7780-1
4L Canister plastic	AU7780-4
10L Canister plastic	AU7780-10
20L Canister plastic	AU7780-20
200L Barrel	AU7780-200

UFI: KU20-M02T-V00X-NKDD

*The document is for informational purposes and is not an official certificate. The data is based on production control and corresponds to the product's characteristics at the time of manufacture.

AUTOLIVE 2015 S.L.
Av. Fuentemar 43, Nave 9-A
28823 COSLADA, MADRID - ESPAÑA

Nika-Trade LLP, 35a Almatyskaya str,
m. Kyiv, 02092, Ukraine
+38(044) 500-55-04

AUTOLIVE