

Product information*

GEAR 75W-80



Description

GEAR 75W-80 is a universal energy-saving synthetic gear oil. It can be used in all manual transmissions, including 5- and 6-speed manual transmissions. It provides significant fuel economy and smooth gear shifting. It has excellent anti-wear properties, which significantly extends the service life of the equipment. It is intended for all types of equipment: on-road (mainline tractors, buses), off-road (construction, mining, agricultural) and special vehicles requiring GL-4 and below and/or GL-5 performance levels.



Specifications / Approvals

API GL-4/GL-5 LS

Also recommend this product for vehicles or assemblies for which the following specifications or original part numbers are required

MIL-L 2105C, FORD WSD-M2C200-C, MACK GO-J PLUS, PSA B71 2330

Technical data*

Viscosity at 100 °C	ASTM D 445 8,87 mm ² /s
Viscosity index	ASTM D 2270 TS ISO 2909 144
Solidification temperature	ASTM D 97 -29°C
Density at 15 °C	ASTM D 1298 0,859 g/cm ³

Available pack sizes

1L Canister plastic	AU8001-1
4L Canister plastic	AU8001-4

*The document is for informational purposes and is not an official certificate. The data is based on production control and corresponds to the product's characteristics at the time of manufacture.

AUTOLIVE 2015 S.L.
Av. Fuentemar 43, Nave 9-A
28823 COSLADA, MADRID - ESPAÑA

Nika-Trade LLP, 35a Almatyskaya str,
m. Kyiv, 02092, Ukraine
+38(044) 500-55-04

AUTOLIVE