

Product information*

PREMIUM 5W-30



Description

PREMIUM 5W-30 is a fully synthetic premium motor oil. Ideal for use in engines with high technical performance, including multi-valve and high-speed petrol and diesel engines, both with and without turbocharging. It has excellent viscosity stability at high operating temperatures. Keeps the engine absolutely clean.



Specifications / Approvals

API SN/CF, ACEA A3/B4

Also recommend this product for vehicles or assemblies for which the following specifications or original part numbers are required

VW 502.00/505.00, MB 229.5, Renault RN 0700/RN 0710

Technical data*

Viscosity at 100 °C	ASTM D 445 11,98 mm ² /s
Viscosity index	ASTM D 2270 TS ISO 2909 156
Solidification temperature	ASTM D 97 -32°C
Density at 15 °C	ASTM D 1298 0,858 g/cm ³
TBN	ASTM D2896 TS 5655 ISO 3771 7,7 mgKOH/g

Available pack sizes

1L Canister plastic	AU7779-1
4L Canister plastic	AU7779-4
10L Canister plastic	AU7779-10
20L Canister plastic	AU7779-20
200L Barrel	AU7779-200

*The document is for informational purposes and is not an official certificate. The data is based on production control and corresponds to the product's characteristics at the time of manufacture.

AUTOLIVE 2015 S.L.
Av. Fuentemar 43, Nave 9-A
28823 COSLADA, MADRID - ESPAÑA

Nika-Trade LLP, 35a Almatyskaya str,
m. Kyiv, 02092, Ukraine
+38(044) 500-55-04

AUTOLIVE