

Product information*

PREMIUM ULTRA 5W-30



Description

PREMIUM ULTRA 5W-30 is a fully synthetic premium motor oil. Ideal for use in engines with high technical performance, including multi-valve and high-speed petrol and diesel engines, both with and without turbocharging. It has excellent viscosity stability at high operating temperatures. Keeps the engine absolutely clean.



Specifications / Approvals

API SN/CF, ACEA C2/C3

Also recommend this product for vehicles or assemblies for which the following specifications or original part numbers are required

VW 504.00/507.00, MB 229.51/229.52, GM dexos2

Technical data*

Viscosity at 40 °C	ASTM D 445 61,47 mm ² /s
Viscosity at 100 °C	ASTM D 445 10,83 mm ² /s
Viscosity index	ASTM D 2270 TS ISO 2909 169
Solidification temperature	ASTM D 97 -38°C
Density at 15 °C	ASTM D 1298 0,863 g/cm ³
TBN	ASTM D2896 TS 5655 ISO 3771 7,6 mgKOH/g

Available pack sizes

1L Canister plastic	AU7778-1
5L Canister plastic	AU7778-5
20L Canister plastic	AU7778-20
200L Barrel	AU7778-200

UFI: HX50-TOX3-WOOR-FVCQ

*The document is for informational purposes and is not an official certificate. The data is based on production control and corresponds to the product's characteristics at the time of manufacture.

AUTOLIVE 2015 S.L.
Av. Fuentemar 43, Nave 9-A
28823 COSLADA, MADRID - ESPAÑA

Nika-Trade LLP, 35a Almatyskaya str,
m. Kyiv, 02092, Ukraine
+38(044) 500-55-04

AUTOLIVE