

Product information*

SUPER SHPD DIESEL 15W-40



Description

SUPER SHPD DIESEL 15W-40 is a premium multigrade engine oil for all types of diesel engines in trucks, buses, tractors and road vehicles with and without turbocharging. The oil provides reliable use in extreme operating conditions. This series of lubricants is specially formulated to meet the latest ACEA, API and vehicle manufacturer (OEM) requirements. It is made on the basis of base oils and a balanced package of high-quality additives from leading world manufacturers. It provides optimum lubrication and significantly extends drain intervals.



Specifications / Approvals

API CI-4/SL, ACEA E7

Also recommend this product for vehicles or assemblies for which the following specifications or original part numbers are required

VOLVO VDS-3, MB 228.3, MAN M 3275-1, RENAULT TRUCKS RD-2, RLD-2
DETROIT DIESEL 93K215, CUMMINS CES 20077

Technical data*

Viscosity at 40 °C	ASTM D 445 109,3 mm ² /s
Viscosity at 100 °C	ASTM D 445 14,58 mm ² /s
Viscosity index	ASTM D 2270 TS ISO 2909 137
Solidification temperature	ASTM D 97 -28°C
Density at 15 °C	ASTM D 1298 0,867 g/cm ³
TBN	ASTM D2896 TS 5655 ISO 3771 12,9 mgKOH/g

Available pack sizes

5L Canister plastic	AU8013-5
10L Canister plastic	AU8013-10
20L Canister plastic	AU8013-20
200L Barrel	AU8013-200

UFI: A830-40HT-E00E-Y99Q

*The document is for informational purposes and is not an official certificate. The data is based on production control and corresponds to the product's characteristics at the time of manufacture.

AUTOLIVE 2015 S.L.
Av. Fuentemar 43, Nave 9-A
28823 COSLADA, MADRID - ESPAÑA

Nika-Trade LLP, 35a Almatyskaya str,
m. Kyiv, 02092, Ukraine
+38(044) 500-55-04

AUTOLIVE