

# Product information\*

## ATF DEXRON II D



### Description

ATF DEXRON II D is a gear oil for automatic transmissions, servo drives (power steering) and industrial units in which the use of Dexron II D type fluids is recommended. The high-quality additive package ensures no foaming, good wear resistance, reliable operation and helps to increase the service life of equipment under high loads in a wide temperature range. When using it, it is necessary to follow the recommendations of car, gearbox and hydraulic system manufacturers.



### Specifications / Approvals

Allison C3/C4

**Also recommend this product for vehicles or assemblies for which the following specifications or original part numbers are required**

MB 236.6, ZF TE-ML04D

### Technical data\*

### Available pack sizes

Viscosity at 40 °C	ASTM D 445 TS 1451 EN ISO 3104 42,47 mm <sup>2</sup> /s	1L Canister plastic	AU8022-1
Viscosity at 100 °C	ASTM D 445 TS 1451 EN ISO 3104 7,22 mm <sup>2</sup> /s	10L Canister plastic	AU8022-10
Viscosity index	ASTM D 2270 TS ISO 2909 133	20L Canister plastic	AU8022-20
Solidification temperature	ASTM 6749 -29°C	200L Barrel	AU8022-200
Density at 15 °C	ASTM D 7777 TS EN ISO 12185 0,859 g/cm <sup>3</sup>		

**UFI:** VK20-300 M-YOOF-PJN6

\*The document is for informational purposes and is not an official certificate. The data is based on production control and corresponds to the product's characteristics at the time of manufacture.

**AUTOLIVE 2015 S.L.**  
Av. Fuentemar 43, Nave 9-A  
28823 COSLADA, MADRID - ESPAÑA

**Nika-Trade LLP, 35a Almatyskaya str,**  
m. Kyiv, 02092, Ukraine  
+38(044) 500-55-04

**AUTOLIVE**