

Product information*

ATF DEXRON III H



Description

ATF DEXRON III H is a high-quality gear oil for automatic transmissions of cars, trucks, buses and industrial equipment. It can also be used in hydrodynamic transformers, hydraulic and power steering drives in accordance with the manufacturer's instructions. It provides smooth gear shifting at low temperatures due to its high coefficient of friction. It is made on the basis of high-quality base oil with PAO and a modern additive package. It has good resistance to ageing and oxidation.



Specifications / Approvals

Allison C4, Allison TES 389

Also recommend this product for vehicles or assemblies for which the following specifications or original part numbers are required

ZF TE-ML 04D, 14A, MB 236.9, Voith H55.6335.xx

Technical data*

Viscosity at 40 °C	ASTM D 445 40,95 mm ² /s
Viscosity at 100 °C	ASTM D 445 7,51 mm ² /s
Viscosity index	ASTM D 2270 TS ISO 2909 152
Solidification temperature	ASTM D 97 -38°C
Density at 15 °C	ASTM D 1298 0,853 g/cm ³

Available pack sizes

1L Canister plastic	AU8010-1
10L Canister plastic	AU8010-10
20L Canister plastic	AU8010-20
200L Barrel	AU8010-200

*The document is for informational purposes and is not an official certificate. The data is based on production control and corresponds to the product's characteristics at the time of manufacture.

AUTOLIVE 2015 S.L.
Av. Fuentemar 43, Nave 9-A
28823 COSLADA, MADRID - ESPAÑA

Nika-Trade LLP, 35a Almatyskaya str,
m. Kyiv, 02092, Ukraine
+38(044) 500-55-04

AUTOLIVE