

# Product information\*

## COMPRESSOR OIL ISO 46



### Description

COMPRESSOR OIL ISO 46 is a highly refined, paraffinic, low-ash mineral compressor oil with an extended drain interval. It ensures stable and uninterrupted operation of the equipment throughout its entire service life. It has anti-corrosion and anti-foam properties, low volatility and excellent oxidation and ageing resistance. It guarantees minimal formation of sediment and deposits. It has cooling properties. Compatible with all sealing materials. It is suitable for all types of reciprocating and rotary compressors with an outlet air temperature of up to 220°C. It is approved for use in hydraulic systems as a low-ash oil.



**Also recommend this product for vehicles or assemblies for which the following specifications or original part numbers are required**

SO-L DAA, DAB, DAH, DAG, DIN 51 506 VBL, VCL, VDL

### Technical data\*

Viscosity at 100 °C	ASTM D 445 7,17 mm <sup>2</sup> /s
Viscosity index	ASTM D 2270 TS ISO 2909 107
Solidification temperature	ASTM D 97 -28°C
Density at 15 °C	ASTM D 1298 0,851 g/cm <sup>3</sup>

### Available pack sizes

1L Canister plastic	AU8012-1
20L Canister plastic	AU8012-20

\*The document is for informational purposes and is not an official certificate. The data is based on production control and corresponds to the product's characteristics at the time of manufacture.

AUTOLIVE 2015 S.L.  
Av. Fuentemar 43, Nave 9-A  
28823 COSLADA, MADRID - ESPAÑA

Nika-Trade LLP, 35a Almatyskaya str,  
m. Kyiv, 02092, Ukraine  
+38(044) 500-55-04

# AUTOLIVE