

Product information*

EXTRA GEAR GL-5 80W-90



Description

EXTRA GEAR GL-5 80W-90 is a high-performance gear oil developed using the most advanced technologies. It is used in all types of gears where the use of API GL-5 oil is recommended. It is recommended for hypoid gears, passenger cars, vans, trucks and buses. It has excellent thermal stability and oxidation resistance, prevents the formation of deposits and thickening of the lubricant, and extends the service life of the transmission. It provides stable viscosity, ensuring reliable operation of transmission parts in winter.



Specifications / Approvals

API GL-5 LS

Also recommend this product for vehicles or assemblies for which the following specifications or original part numbers are required

MIL-L2105 D, MAN 342, MB 235.0

Technical data*

Viscosity at 100 °C	ASTM D 445 16,40 mm ² /s
Viscosity index	ASTM D 2270 TS ISO 2909 97
Solidification temperature	ASTM D 97 -25°C
Density at 15 °C	ASTM D 1298 0,870 g/cm ³

Available pack sizes

1L Canister plastic	AU7789-1
20L Canister plastic	AU7789-20
200L Barrel	AU7789-200

UFI: VX20-30S7-600E-AWYF

*The document is for informational purposes and is not an official certificate. The data is based on production control and corresponds to the product's characteristics at the time of manufacture.

AUTOLIVE 2015 S.L.
Av. Fuentemar 43, Nave 9-A
28823 COSLADA, MADRID - ESPAÑA

Nika-Trade LLP, 35a Almatyskaya str,
m. Kyiv, 02092, Ukraine
+38(044) 500-55-04

AUTOLIVE