

Product information*

HYDRO ISO 46 HLP



Description

HYDRO ISO 46 HLP is a high-quality mineral-based multigrade hydraulic oil with highly effective wear-reducing additives. It contains active chemicals to improve properties such as resistance to ageing and high pressure, and has exceptional anti-corrosion and detergent-dispersant properties. It is used in all modern hydraulic systems of construction and mining equipment designed for heavy-duty working conditions, including high-speed and high-pressure vane, gear and axial piston pumps of hydraulic systems.



Also recommend this product for vehicles or assemblies for which the following specifications or original part numbers are required

MAGIAS P68-P69-P70, AFNOR NF E 48603 HM, Eaton Vickers 1286S (Industrial), M-2950-S (Mobile), DIN 51524 Part 2 HLP PARKER DENISON HF0, HF1, HF2 ISO 6743/4 HM

Technical data*

Viscosity at 40 °C	ASTM D 445 TS 1451 EN ISO 3104 45,40 mm ² /s
Viscosity at 100 °C	ASTM D 445 TS 1451 EN ISO 3104 6,95 mm ² /s
Viscosity index	ASTM D 2270 TS ISO 2909 110
Solidification temperature	ASTM 6749 -30°C
Density at 15 °C	ASTM D 7777 TS EN ISO 12185 0,862 g/cm ³

Available pack sizes

10L Canister plastic	AU7787-10
20L Canister plastic	AU7787-20
200L Barrel	AU7787-200

UFI: A030-MOFM-GOOX-Y8JH

*The document is for informational purposes and is not an official certificate. The data is based on production control and corresponds to the product's characteristics at the time of manufacture.

AUTOLIVE 2015 S.L.
Av. Fuentemar 43, Nave 9-A
28823 COSLADA, MADRID - ESPAÑA

Nika-Trade LLP, 35a Almatyskaya str,
m. Kyiv, 02092, Ukraine
+38(044) 500-55-04

AUTOLIVE