

Product information*

TURBO 5W-40



Description

TURBO 5W-40 is a fully synthetic high-performance diesel engine oil that helps to extend engine life while providing fuel economy for modern diesel engines operating in heavy-duty applications. It is recommended for use in a wide range of light-duty applications such as turbocharged pick-up trucks, as well as for heavy-duty and off-road applications such as road transport, construction and agricultural applications. It helps maintain performance at significantly higher temperatures than other high-performance diesel engine oils.



Specifications / Approvals

API CI-4/SN, ACEA A3/B4

Also recommend this product for vehicles or assemblies for which the following specifications or original part numbers are required

BMW Longlife-04, Fiat 9.55535-S2, Ford WSS-M2C917-A, MB 229.31/229.51/226.5, Renault RN 0700/0710, VW 502.00/505.00/505.01

Technical data*

Viscosity at 100 °C	ASTM D 445 14,00 mm ² /s
Viscosity index	ASTM D 2270 TS ISO 2909 164
Solidification temperature	ASTM D 97 -30°C
Density at 15 °C	ASTM D 1298 0,860 g/cm ³
TBN	ASTM D2896 TS 5655 ISO 3771 10,7 mgKOH/g

Available pack sizes

1L Canister plastic	AU7781-1
5L Canister plastic	AU7781-5
10L Canister plastic	AU7781-10
20L Canister plastic	AU7781-20
200L Barrel	AU7781-200

*The document is for informational purposes and is not an official certificate. The data is based on production control and corresponds to the product's characteristics at the time of manufacture.

AUTOLIVE 2015 S.L.
Av. Fuentemar 43, Nave 9-A
28823 COSLADA, MADRID - ESPAÑA

Nika-Trade LLP, 35a Almatyskaya str,
m. Kyiv, 02092, Ukraine
+38(044) 500-55-04

AUTOLIVE