

Product information*

HIGH TEMPERATURE GREASE LC-2



Description

High-temperature multi-purpose grease based on mineral oils with the addition of special antioxidant and anticorrosive additives. Specially designed to withstand high temperatures and extreme loads. Retains its operational properties at high temperatures, which increases the service life of bearings. Designed for use in all types of automotive equipment and for general industrial use. The consistency of the lubricant remains constant during long-term storage.



Specifications / Approvals

NLGI 2, DIN51502, KP2P-30, MB 265.1, MAN TL 284

Operating temperature range

Max. working temperature: 260°C

Technical data*

Colour: Blue

Composition:

CAS#74869-22-0	Base oil
CAS#10254-57-6	Dialkyl dithiocarbamate
CAS#1310-65-2	Lithium hydroxide
CAS#106-14-9	12-hydroxystearic acid

UFI: DN70-X0R2-100N-PQ10

Available pack sizes

0,39KG Tubes	A401
4,5KG Plastic bucket	A401/2
17KG Plastic bucket	A401/3



*The document is for informational purposes and is not an official certificate. The data is based on production control and corresponds to the product's characteristics at the time of manufacture.

AUTOLIVE 2015 S.L.
Av. Fuentemar 43, Nave 9-A
28823 COSLADA, MADRID - ESPAÑA

Nika-Trade LLP, 35a Almatyskaya str,
m. Kyiv, 02092, Ukraine
+38(044) 500-55-04

AUTOLIVE