

Product information*

PAO CLP 220



Description

PAO CLP 220 is a high-quality extreme pressure oil produced on the basis of high-quality synthetic oils and PAO base materials. It provides improved load-bearing capacity, excellent wear and corrosion protection, high viscosity index and flash point, and low pour point. PAO CLP 220 is used in industrial equipment operating in harsh environments and extreme temperature conditions. It is recommended for enclosed industrial gearboxes and bearings, especially where they are subjected to severe loads such as heavy load, low speed, shock loads and wide temperature extremes.



Specifications / Approvals

ISO VG 220, AGMA 9005-D94, DIN 51517-3

Also recommend this product for vehicles or assemblies for which the following specifications or original part numbers are required

Cincinnati Milacron, Clean Panel Coker, US Steel 224, US Steel S-200

Technical data*

Available pack sizes

Viscosity at 40 °C	ASTM D 445 TS 1451 EN ISO 3104 195,2 mm ² /s	20L Canister plastic	AU7791-20
Viscosity at 100 °C	ASTM D 445 TS 1451 EN ISO 3104 30,59 mm ² /s		
Viscosity index	DIN ISO 2909:2004-08 200		
Solidification temperature	ASTM D 7346:2015 -29°C		
Density at 15 °C	DIN EN ISO 12185:1997-11 863 kg/m ³		

*The document is for informational purposes and is not an official certificate. The data is based on production control and corresponds to the product's characteristics at the time of manufacture.

AUTOLIVE 2015 S.L.
Av. Fuentemar 43, Nave 9-A
28823 COSLADA, MADRID - ESPAÑA

Nika-Trade LLP, 35a Almatyskaya str,
m. Kyiv, 02092, Ukraine
+38(044) 500-55-04

AUTOLIVE